

# ONE-BOX

## LED EXIT SIGN WITH EMERGENCY DOWNLIGHT



### PICTOGRAMS INCLUDED



240V 50Hz	5W TOTAL WATTAGE	2W MAINTD LAMP	1W NON-MTD LAMP				CRI >80	Ta 40°C	C0: E12.5 C90: E12.5	AS/NZS APPROVED
--------------	------------------------	----------------------	-----------------------	--	--	--	------------	------------	-------------------------	--------------------

The One-Box is a general purpose, double or single-sided interior ceiling or wall mounted exit sign with an additional 1W emergency downlight. For use at doorway, stairways, corridors and intersection on an emergency escape route.

The One-Box exit sign incorporates an integral emergency 2 hour battery pack that permits self-powered operation during power outages.

### FEATURES

- Compliant to AS/NZS 2293
- 50,000 Hour average life rated LED modules
- Surface-mount Ceiling or Wall
- Injection moulded polycarbonate housing and acrylic diffuser with pictogram legends
- Viewing distance 24M
- High density storage LiCoO2 batteries
- Diffuser & pictogram inserts included
- IP20 rating
- Additional 1W Non-Maintained downlight during mains power outage
- 2 Hour duration period
- TA40 - maximum thermal ambient operating temperature
- Charger type: Trickle
- Charger time: 16 Hours
- Charger operation: Continuous

### APPLICATIONS

Doorways, stairways, corridors and intersections on an emergency escape route.

### CLASSIFICATION & SPACING DISTANCE

Model	Mounting Height in Metres										
	Plane	Class	2.1	2.4	2.7	3.0	3.6	4.0	4.5	5.0	6.0
19876	C0	E12.5	8.0	8.8	9.4	10.0	10.4	11.0	11.4	12.0	12.4
	C90	E12.5	8.0	8.8	9.4	10.0	10.4	11.0	11.4	12.0	12.4

MODEL NO.	MAINTAINED LAMP WATTAGE (W)	NON-MAINTAINED LAMP WATTAGE (W)	FITTING COLOUR
19876/..	2	1	/05-WHITE

